



HORTI

MASTER GreenPower CG T 250W E40 1SL/12

High Pressure Sodium lamp with clear outer bulb, optimized growthlight output and maintenance

Product data


General Information		Electrical	
Cap-Base	E40 [E40]	Ignition Peak Voltage (Max)	2800 V
Bulb Shape	T46 [T 46mm]	Re-Ignition Time (Min) (Max)	120 min
Operating Position	UNIVERSAL [Any or Universal (U)]	Ignition Time (Max)	10 s
Life To 5% Failures (Nom)	16000 h	Voltage (Max)	129 V
Life To 20% Failures (Nom)	26000 h	Voltage (Min)	99 V
Life To 50% Failures (Nom)	32000 h	Voltage (Nom)	114 V
System Description	System 230V		
Light Technical		Controls and Dimming	
Color Code	220 [CCT of 2000K]	Dimmable	Yes
Luminous Flux (Rated) (Nom)	33300 lm	Run-Up Time 90% (Max)	5 min
Photosynthetic Photon Flux (PPF)	422 μmol/s		
Correlated Color Temperature (Nom)	2000 K	Mechanical and Housing	
Luminous Efficacy (rated) (Nom)	124.7 lm/W	Bulb Finish	Clear
Color Rendering Index (Max)	-	Cap-Base Information	-
Color Rendering Index (Nom)	29		
Operating and Electrical		Approval and Application	
Lamp supply voltage	230 V [230]	Energy Efficiency Label (EEL)	A+
Power (Rated) (Min)	267.0 W	Mercury (Hg) Content (Nom)	15 mg
Power (Rated) (Nom)	267.0 W	Energy Consumption kWh/1000 h	293 kWh
Lamp Current (EM) (Nom)	2.8 A		
Ignition Supply Voltage (Max)	198 V	Luminaire Design Requirements	
		Bulb Temperature (Max)	450 °C
		Cap-Base Temperature (Max)	250 °C

Product Data

Full product code	872790085775700
Order product name	MASTER GreenPower CG T 250W E40 1SL/12
EAN/UPC - Product	8727900857757
Order code	928197109227
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	12
Material Nr. (12NC)	928197109227
Net Weight (Piece)	0.175 kg
ILCOS Code	ST-250-H/S-E40

Dimensional drawing



SON GreenPower CG T 250W E40

Product	D	O	L	C	A
---------	---	---	---	---	---

