

SHP-T GroExpress

SHP-T 600W GROXPRESS E40

0020818



Product features

-



PRODUCT OVERVIEW

Lamp finish	Clear
Lamp shape	High Pressure Sodium
Colour temperature (K)	2050
CRI (Ra)	20
Dimmable	Yes
EAN code	5410288208183
Energy class	A++
Cap/Base	E40
Beam angle(°)	-
Type	SHP-T
Watt (Nominal) (W)	600
Light colour	Meat
Ordering number	0020818
Efficacy (Rated) (lm/w)	145
Average life (h) - L70/B50	24000
Luminous flux (Rated) (lm)	90000
Technology	HID

DATA TABLE

Optical data

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	2050
CRI (Ra)	20
Beam angle(°)	-
Light colour	Meat
Luminous flux (Nominal) (lm)	90000

SHP-T GroExpress

SHP-T 600W GROXPRESS E40

0020818

Rated lumen maint. factor at 12000 h 50Hz	0.9
Rated lumen maint. factor at 16000 h 50Hz	0.88
Rated lumen maint. factor at 20000 h 50Hz	0.86
Rated lumen maint. factor at 2000 h 50Hz	0.97
Rated lumen maint. factor at 4000 h 50Hz	0.96
Rated lumen maint. factor at 6000 h 50Hz	0.95
Rated lumen maint. factor at 8000 h 50Hz	0.93
Luminous flux (Rated) (lm)	90000

General data

Average life (h) at Ta 25° C	24000
Control gear required	yes
Lamp finish	Clear
Lamp shape	High Pressure Sodium
Dimmable	Yes
EAN code	5410288208183
Energy class	A++
General application	Logistics and Industry; Outdoor
IEC Reference	IEC 60662
IEC Reference 2	IEC 62035
Intended purpose	Special lighting
Cap/Base	E40
Lamp mercury content (mg)	24
Type	SHP-T
Ordering number	0020818
Product name	SHP-T 600W GROXPRESS E40
Average life (h) - L70/B50	24000
Rated survival factor at 12000 h 50Hz	0.93
Rated survival factor at 16000 h 50Hz	0.9
Rated survival factor at 20000 h 50Hz	0.86
Rated survival factor at 2000 h 50Hz	1
Rated survival factor at 4000 h 50Hz	0.99
Rated survival factor at 6000 h 50Hz	0.98
Rated survival factor at 8000 h 50Hz	0.97
Technology	HID
Transformer required	no
Photosynthetically active radiation (PAR)	950

SHP-T GroExpress

SHP-T 600W GROXPRESS E40

0020818

Photosynthetic Photon Flux (PPF) 165000
(phyto-lm)

Electrical data


Current (A)	5.8
Ignition voltage (V)	0
kWh per 1000 hours burning time	660
Watt (Nominal) (W)	600
Efficacy (Rated) (lm/w)	145
Watt (Rated) (W)	600

Physical data

Max. Lamp Diameter (mm) - D	48
Lamp Length (mm) - C/L	292
Length base to pin Min-Max - B	853.7-856.1

TECHNICAL DRAWINGS

E40



SHP-T GroExpress
SHP-T 600W GROXPRESS E40
0020818

