



MASTER TL-D Super 80

MASTER TL-D Super 80 18W/840 1SL/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Product data

General Information		Color Rendering Index (Nom)	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Color Rendering Index (Nom)	85
Bulb Shape	T8 [26 mm (T8)]	LLMF 2000 h Rated	96 %
Life To 10% Failures (Nom)	12000 h	LLMF 4000 h Rated	95 %
Life To 50% Failures (Nom)	15000 h	LLMF 6000 h Rated	94 %
Life To 50% Failures Preheat (Nom)	20000 h	LLMF 8000 h Rated	93 %
LSF 2000 h Rated	99 %	LLMF 12000 h Rated	92 %
LSF 4000 h Rated	99 %	LLMF 16000 h Rated	91 %
LSF 6000 h Rated	99 %	LLMF 20000 h Rated	90 %
LSF 8000 h Rated	99 %		
LSF 12000 h Rated	89 %	Operating and Electrical	
LSF 16000 h Rated	33 %	Power (Rated) (Nom)	18 W
LSF 20000 h Rated	2 %	Lamp Current (Nom)	0.360 A
		Temperature	
		Design Temperature (Nom)	25 °C
		Controls and Dimming	
		Dimmable	Yes
		Mechanical and Housing	
		Cap-Base Information	Green Plate

MASTER TL-D Super 80

Approval and Application


Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	2.0 mg
Energy Consumption kWh/1000 h	22 kWh

Product Data

Full product code	871150063171840
Order product name	MASTER TL-D Super 80 18W/840 1SL/25
EAN/UPC - Product	8711500631718

Order code	927920084023
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	927920084023
Net Weight (Piece)	71.000 g
ILCOS Code	FD-18/40/1B-E-G13

Dimensional drawing



Product	D	A	B	B	C
MASTER TL-D Super 80 18W/840 1SL/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

TL-D 18W/840

