

## T5 FHE Luxline Plus

21W/T5/830 FHE

**0002763**



### Product features

- 



### PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	T5
Colour temperature (K)	3000
CRI (Ra)	85
EAN code	5410288027630
Energy class	A+
Cap/Base	G5
Type	T5 FHE Luxline Plus
Watt (Nominal) (W)	21
Light colour	830 Warm White
Ordering number	0002763
Efficacy (Rated) (lm/w)	92
Average life (h) - L70/B50	24000
Luminous flux (Rated) (lm)	1900
Technology	Fluorescent

### DATA TABLE

#### Optical data

Ambient temperature for maximum luminous flux (°C)	35
Colour temperature (K)	3000
CRI (Ra)	85
Light colour	830 Warm White
Luminous flux (Nominal) (lm)	1900
Luminous flux (Nominal) at 35°C (lm)	2100
Rated lumen maint. factor at 12000 h 50Hz	0.91
Rated lumen maint. factor at 16000 h 50Hz	0.9

## T5 FHE Luxline Plus

21W/T5/830 FHE

**0002763**

Rated lumen maint. factor at 20000 h 50Hz	0.88
Rated lumen maint. factor at 2000 h 50Hz	0.97
Rated lumen maint. factor at 4000 h 50Hz	0.95
Rated lumen maint. factor at 6000 h 50Hz	0.93
Rated lumen maint. factor at 8000 h 50Hz	0.92
Luminous flux (Rated) (lm)	1900

### General data

Average life (h) at Ta 25° C	24000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	T5
EAN code	5410288027630
Energy class	A+
Fixture rating	Open

### General application

Retail;  
Hospitality;  
Logistics and Industry;  
Museums;  
Education;  
Office;  
Residential & Consumer;

IEC Reference	IEC 60081
IEC Reference 2	IEC 61195
Intended purpose	General lighting
Cap/Base	G5
Lamp mercury content (mg)	2.3
Type	T5 FHE Luxline Plus
Ordering number	0002763
Product name	21W/T5/830 FHE
Average life (h) - L70/B50	24000
Rated survival factor at 12000 h 50Hz	0.93
Rated survival factor at 16000 h 50Hz	0.9
Rated survival factor at 20000 h 50Hz	0.84
Rated survival factor at 2000 h 50Hz	0.99
Rated survival factor at 4000 h 50Hz	0.98
Rated survival factor at 6000 h 50Hz	0.96
Rated survival factor at 8000 h 50Hz	0.94
Special purpose lamp	No
Technology	Fluorescent

## T5 FHE Luxline Plus

21W/T5/830 FHE

**0002763**

<b>Transformer required</b>	No
<b>E-number SE</b>	8356510
<b>E-number FI</b>	4944213


### Electrical data

<b>Current (A)</b>	0.165
<b>Ignition voltage (V)</b>	0
<b>kWh per 1000 hours burning time</b>	23
<b>Watt (Nominal) (W)</b>	21
<b>Efficacy (Rated) (lm/w)</b>	92
<b>Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.</b>	100
<b>Watt (Rated) (W)</b>	21
<b>Watt (Rated) - High frequency (W)</b>	20.7

### Physical data

<b>Max. Lamp Diameter (mm) - D</b>	16
<b>Lamp Length (mm) - C/L</b>	863.2
<b>Length base to base (mm) - A</b>	849
<b>Length base to pin Min-Max - B</b>	853.7-856.1

## TECHNICAL DRAWINGS



## T5 FHE Luxline Plus

21W/T5/830 FHE

**0002763**

